

Dividers

Dividers are used for distributing the extinguishing medium from one feed line over several hose lines, or in special cases for collecting it in the reverse direction. Each hose line can be shut-off individually by means of a stop valve. The stop valve of the dividers must be according to DIN 14365 easily operated in the usual flow direction at 16 bar and in the opposite direction at 6 bar.

Dividers with screw down valves - 2 outlets



3100

Allows smooth opening and closing and can be used as a regulating element.

Storz System Connection or thread

Inlet Storz / thread	Outlet Storz / thread	Bonnets inch	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident-No.	Remarks
45	2 x D	2 x 1"	200	175	145	1,250	60545833	
C	2 x D	2 x 1"	200	175	145	1,200	30042133	
G 2 A	2 x G 1 A	2 x 1"	178	175	140	0,800	60166233	
G 2 A	2 x G 2 A	2 x 2"	255	245	240	2,240	20176233	
C	2 x C	2 x 2"	280	245	240	3,000	60105133	
65	2 x 38	2 x 2"	285	245	240	3,200	60124733	
65	2 x 45	2 x 2"	250	220	240	3,200	60256233	
65	2 x 65	2 x 2"	285	245	240	3,300	60256733	
65	2 x 65	2 x 2"	285	245	240	3,800	60198233	1)
B	2 x C	2 x 2"	285	245	240	3,200	20016433	
B	2 x C	2 x 2"	285	245	240	8,800	20016495	
G 2½ A	2 x G 2 A	2 x 2"	255	245	240	2,250	60027333	
B	2 x B	2 x 2½"	320	285	265	4,500	20097433	
G 2½ A	2 x G 2½ A	2 x 2½"	290	275	265	3,200	60158133	
100	2 x B	2 x 2½"	330	300	280	5,440	20099633	
A	2 x B	2 x 2½"	335	300	280	4,400	20020333	
G 4 A	2 x G 2½ A	2 x 2½"	295	270	280	3,450	60151933	

